

# International Journal on Robotics, Automation and Sciences

## Exploring Recommender Systems in the Healthcare: A Review on Methods, Applications and Evaluations

Su-Cheng Haw\*, Jayapradha Jayaram, Elham Abdulwahab Anaam and Heru Agus Santoso

**Abstract** – Due to the vast amount of publicly available online data, people may find it difficult to obtain relevant information to find food or meals that match their taste and health while maintaining a healthy lifestyle. The overload of information makes it difficult to separate relevant, personalized information from massive volumes of data. Recommendation systems (RS) are suggestion systems that provide users with information that they may be interested in. With RS, this enormous amount of information is filtered and analyzed for further insights. This paper will explore several generations of recommender systems in the healthcare industry. This paper thoroughly analyses the current state-of-the-art recommender systems focusing on the grouping, methods, application and evaluation metrics. In addition, several challenges for further research and improvement in this domain are also outlined in the paper.

**Keywords**—*Recommender System, Recommendation Technique, Evaluation, Traditional Recommender System, Generative AI.*

### I. INTRODUCTION

Recommender systems analyze data intelligently to provide personalized recommendations for services and products [1]. Recommendation systems predict the value or preference that a user will give an item to

generate relevant products or services personalized to each user. Towards recent years, recommender systems have gained popularity in several domains such as food, tourism, social media, movies, e-Commerce, e-learning, news and healthcare.

The vast volume of growing healthcare data [2] publicly made available worldwide indirectly hinders people from accessing important information easily. Since it might be difficult to retrieve information, using a Healthcare Recommender System (HRS) can help to reduce the issue of information overload [3,4]. For instance, by basing on patient data like medical history and demographics, each patient can receive personalised treatment. In addition, recommender systems also aid clinicians in decision-making by recommending medications and treatment plans to the patient. Furthermore, early disease detection could be performed by identifying at-risk individuals and suggesting preventive measures [5]. In particular, recommender systems transform healthcare by tailoring personalized care, improving faster response by providing suggestions and optimizing resource allocation [6,7].

Generally, a typical recommender system is divided into four main groups: content-based, collaborative filtering, hybrid-based and generative AI. Though there are many approaches being published by various researchers, this paper groups and analysis the

\* Corresponding Author email: [sucheng@mmu.edu.my](mailto:sucheng@mmu.edu.my) ORCID: 0000-0002-7190-0837

Su-Cheng Haw is with Faculty of Computing and Informatics, Multimedia University, Cyberjaya, Malaysia (e-mail: [sucheng@mmu.edu.my](mailto:sucheng@mmu.edu.my)).

Jayapradha Jayaram is with Department of Computing Technologies, SRM Institute of Science and Technology, Kattankulathur Chennai, India. (e-mail: [jayapraj@srmist.edu.in](mailto:jayapraj@srmist.edu.in)).

Elham Abdulwahab is with Faculty of Computing and Informatics, Multimedia University, Cyberjaya, Malaysia (e-mail: [anaamelham@gmail.com](mailto:anaamelham@gmail.com)).

Heru Agus Santoso is with Faculty of Computer Science, Universitas Dian Nuswantoro, Semarang, Indonesia (email: [heru.agus.santoso@dsn.dinus.ac.id](mailto:heru.agus.santoso@dsn.dinus.ac.id))

related technologies, proposed method, evaluation metrics and datasets used in the healthcare domain.

depicts a detailed description of each technique, and some research carried out in this domain.

The content-based approach recommends items based on what the user liked or interacted with in the past. It analyzes item features or content and recommends items that share similar attributes. For example, in healthcare, a content-based recommender might suggest medications based on similarities in patient demographics, medical history, or symptoms. Some of the techniques under this group are Term Frequency-Inverse Document Frequency (TF-IDF), Bidirectional Encoder Representations from Transformers (BERT), Latent Dirichlet Allocation (LDA), cosine similarity, word embedding, jaccard similarity, euclidean distance and so on. Table 1 shows a detailed description of each technique and some research carried out in this domain.

**TABLE 1. Content-based approaches with some related research in the healthcare domain.**

Techniques	Description	References
TF-IDF	Weigh the importance of medical terms in patient records, aiding in personalized treatment recommendations based on document similarity.	[8-14]
BERT	Leverages pre-trained language models to understand medical texts, improving diagnosis, treatment recommendations, and patient care through contextual understanding	[14-18]
LDA	Identifies topics in medical documents, helping to organize and recommend relevant content or treatments based on shared thematic similarities among patient records.	[16,19-21]
Cosine Similarity	Quantifies the similarity between patient records based on the cosine of the angle between their feature vectors, aiding in personalized treatment recommendations	[17,22-26]
Word Embedding	Transforms medical text data into dense vector representations, capturing semantic relationships between words and enabling accurate analysis for personalized treatment recommendations	[27-29]
Jaccard Similarity	Measures the similarity between patient records based on the intersection and union of their sets of medical terms, aiding in recommending treatments for similar cases.	[30-32]
Euclidean Distance	Calculates the straight-line distance between patient records' feature vectors, facilitating similarity-based recommendations for treatments.	[33,34]

Collaborative filtering recommends items by leveraging the preferences or behaviours of users with the same interests. It identifies users with similar preferences or interactions to recommend items with which similar users may have been interesting or engaged before. Some of the techniques under this group are Matrix Factorization (MF), Support Vector Decomposition (SVD), deep learning (DL), k-nearest neighbor (KNN), ensemble method and so on. Table 2

**TABLE 2. Collaborative filtering approaches with some related research in the healthcare domain.**

Techniques	Description	References
MF	Decomposes the patient-observation matrix into lower-dimensional matrices to capture latent features, enabling personalized treatment recommendations based on similarities among patient records.	[35-39]
SVD	Decomposes the patient-observation matrix into singular vectors and values, identifying latent factors for accurate personalized treatment recommendations based on similarities.	[40,41]
DL	Extracting complex patterns and relationships to provide personalized treatment recommendations based on individual medical histories and needs.	[42-46]
KNN	Identifies similar patients based on medical profiles and recommends treatments based on the collective preferences of nearest neighbors in the dataset.	[47-50]
Ensemble	Combine predictions from multiple models to generate more accurate and robust recommendations. It leverages the diverse strengths of individual models to enhance overall performance.	[51-53]

Hybrid-based combines some recommendation techniques to overcome the limitations of individual approaches to provide more diverse and accurate suggestions. By doing so, hybrid systems can offer improved recommendations. In the healthcare domain, a hybrid recommender might combine content-based filtering with collaborative filtering to provide more personalized treatment recommendations based on both patient characteristics and similarities to other patients [54-58].

Recently, a growing number of recommender systems in healthcare have been incorporating generative artificial intelligence (AI) to provide personalized recommendations for patients and healthcare professionals [59-61]. Generative Adversarial Network (GAN) and Variational Autoencoder (VAE) are some of the well-known model utilized to generate new content suggestions based on learned patterns [62]. As such, Generative AI is capable to address the "cold start" issue, since new content can be generated with minimum input required. In other words, it can address the challenge of limited data available [63,64]. In addition, more diverse and most probably useful or desired recommendations can be provided to solve complex problems related to health [65,66].

## II. APPLICATIONS AND EVALUATION METRICS

### A. Application of HRS

Personalized Treatment Recommendations: HRSs can suggest personalized treatment plans based on one individual medical history, genetic, and lifestyle factors [8]. For instance, using HRS specific

medication or lifestyle changes can be suggested to a patient based on a patient's well-being profile [67].

**Clinical Decision Support:** Healthcare providers can use recommender system to recommend possible diagnostic tests, screening protocols, and treatment options [68,69]. Clinicians can rely on these recommendations to enhance diagnostic accuracy, particularly in complex medical scenarios with multiple treatment options.

**Chronic Disease Management:** With HRS, patients receive recommendations for personalized care plans for chronic diseases, such as diabetes, cardiovascular, asthma, and others [70]. Such recommendations may include medication, recommended nutrition, physical activity patterns, and further treatment that, if followed over the long term, contributes to improving the patient's health [71].

**Telemedicine and Remote Monitoring:** HRS allows virtual and remote monitoring appointments with the help of devices and develops plans under the influence of informed patients and historical healthcare records and at the patient's availability [72], [73]. This way, HRS applies to ensure that patients receive timely help and counseling when needed, regardless of their location.

**Health Promotion and Disease Prevention:** HRS with the prediction capability can advise on health screenings and vaccinations for early disease prevention. Population health management efforts and disease prevention initiatives are made possible through these systems by targeting specific populations or individuals at higher risk [74,75].

### B. Evaluation Metrics

Several metrics can be used to evaluate the effectiveness of HRS [76-78]. Among some of the common evaluation metrics are Mean Absolute Error (MAE), Root Mean Error Square (RMSE), accuracy, precision, recall, F1 score, Mean Average Precision (MAP), Area under the Curve (AUC) and Confusion Matrix [79-81]. Besides, some other evaluation through user testing can also be conducted. For instance, user satisfaction and engagement can be evaluated through click-through rate [82,83], conversion rate [84] or user feedback survey.

#### 1) MAE

MAE is a primary evaluation measure in HRSs used to measure the performance and accuracy to a system. It is simply an important measure to which one can compare the results of the recommendation algorithms designed for the system. By calculating the mean measure of the absolute distinction between the predicted and actual values, MAE disclosed the customer resemblance to a recommendation. For example, in a medication recommendation system, MAE measures the mean absolute differences between a medication's predicted effectiveness and the same medication's actual effectiveness in real patient data, enabling the healthcare provider to improve the recommendation process.

Moreover, its simplicity and intuitive interpretation make it particularly well-suited for healthcare

applications. It provides a simple measure of the average prediction error without being overly sensitive to outliers or extreme values. This attribute is crucial in healthcare, where individual patient cases can vary widely, and accurate recommendations are essential for ensuring patient safety and well-being. By minimizing MAE, HRSs can optimize their recommendations to match patients with the best suitable treatments, ultimately improving patient satisfaction and reducing the risk of adverse events or ineffective treatments.

#### 2) RMSE

RMSE is the measure used to quantify the average error between the predicted health outcomes recommended by the system and those observed. It quantifies the differences between the observed and recommended output generated from the system. This is done by squaring the differences to ensure the positive and negative errors counterbalance each other. Later, the mean is computed, after which the RMSE is taken as the square root.

In practicality, a lower RMSE value represents the close recommendation to the desired if it was taking actual data. This, therefore, shows the system's accuracy in recommending the users closer to their goal. On the other hand, a higher RMSE value represents a bigger deviation and error from the observed values. This value would thus necessitate an improvement of the system, which might be aligned with the algorithm or more accurate input by incorporating more relevant data sources.

#### 3) Accuracy

In HRSs, accuracy serves as a crucial evaluation metric to assess the system's ability to provide precise recommendations. The accuracy metric measures the proportion of correctly predicted recommendations among all recommendations made by the system. In the context of healthcare, where the consequences of incorrect recommendations can be severe, ensuring high accuracy is paramount. A high accuracy score indicates that the recommender system effectively identifies and suggests relevant options that align with patients' needs, preferences, and medical conditions. This metric enables healthcare providers to gauge the reliability and trustworthiness of the recommendations.

#### 4) Precision

Precision is the percentage of relevant items the system recommends compared to the number of all recommended items. The rationale for using precision is that it guarantees that treatment, medicine, or a given provider recommended indeed corresponds to the patient's needs and conditions. Additionally, high precision means that the system recommends the most relevant and appropriate options, which lessens the possibility of error in the decision-making and quality of treatment for patients. Implying precision will promote trust between the HRS and its users, encourage them to make more unbiased decisions, and consequently, secure a positive outcome for patients.

5) *Recall*

Recall scores the ability of the system to recall all relevant items from all the relevant items that are available. In the case of healthcare, it allows adequate recognition to ensure no suitable treatment, medication, or health care providers are left out. A high recall score ensures the recommender system identifies nearly all relevant options, which assures one hardly misses out on significant medical records. It provides confidence in the HRSs and the users to research more before concluding, resulting in better patient care outcomes.

6) *F1 score*

F1 score provides a symmetrical appraisal of both precision and recall. The F1 score aggregates precision and recall into a single measure; hence, a good F1 score means that the healthcare recommender system has achieved a balance between precision and recall. F1 score allows for a complete assessment of the two metrics described above. A high F1 score shows that the healthcare recommender system combines high precision in accurately selecting relevant sets of alternatives and high recall in returning a large fraction of the relevant object sets. Therefore, it will improve the quality of patient care and support clinical decision-making.

7) *MAP*

The MAP provides an indication of how relevant recommended items are and how accurately they are ranked. It measures the average precision on different levels of recall, showing how well the system optimizes and ranks relevant treatments, drugs, or healthcare providers. By binding the precision and recall at different thresholds, the MAP levelled indicates how well the system performs overall. A higher score on MAP indicates that the recommender system identifies logical options and sorts them efficiently, making clinical insights more beneficial and accurate in their prescriptions.

8) *AUC*

The Area Under the Curve (AUC) quantifies the model's ability to discriminate between positive and negative instances, reflecting the system's ability to rank relevant items higher than irrelevant ones across various thresholds. A high AUC score indicates that the recommender system effectively distinguishes between relevant and irrelevant options, thereby enhancing the quality of recommendations and supporting informed decision-making by healthcare professionals.

9) *Confusion Matrix*

The confusion matrix presents a detailed view of how well the system opens the recommendation: it contains information about true-positive, false negative, false-positive, and true-negative recommendations. It shows how the system prioritizes options, rates accuracy, and makes its recommendations. By analyzing the confusion matrix, stakeholders can refine the recommender system's

algorithms and parameters to deliver a better HRS to the patients and healthcare providers.

10) *Mean Squared Error (MSE)*

MSE is the average squared difference between the predicted value and the actual value. Therefore, it should minimize MSE, guaranteeing that the recommender system will create predictions much closer to what the patient intends or prefers.

11) *Mean Absolute Percentage Error (MAPE)*

MAPE is the average percentage difference between predicted and actual recommendations. MAPE should be minimized to ensure the recommender system creates predictions much closer to their medical needs. In other words ensuring that the quality of recommendations is much assured to that the patient's health outcome can be realized.

Figure 1 depicts the word cloud for the evaluation metrics elaborated above. As can be seen, the most utilized evaluation metrics for HRS is RMSE, followed by MAE, while the least utilized metrics are click-through rate and conversion rate.



FIGURE 1. Word count of evaluation metrics in HRS.

### III. RELATED WORKS

Research on healthcare recommender systems has gained traction in recent years due to their potential to enhance patient care and treatment outcomes. Various studies have explored different aspects of these systems, focusing on personalized treatment recommendations, clinical decision support, patient engagement, and resource optimization in healthcare settings. For instance, a personalised and well-designed doctor recommendation system called iDoctor is proposed [85]. It is capable of doing sentiment analysis of text, topic models, matrix factorization, and other approaches on crowdsourced reviews of healthcare products. Sentiment analysis is required to determine the offset for changing the initial rating by taking into account the emotional offset in patient feedback regarding the doctor. iDoctor consists of hybrid model: (1) an LDA model to extract subjects related to user preference and user review comments on specific doctors, and (2) Hybrid Matrix Factorization (HMF) to generate a more personalised recommendation based on user preference and doctor features. By selecting the optimal parameters, it showed improvement as it yields a lower Root Mean Square Error (RMSE). The experiment's results

indicate that the HMF model outperforms the other models, with a significantly lower RMSE, demonstrating the ability of iDoctor to provide more precise doctor recommendations.

Kaur et al. introduced a multi-party Arbitrary Distributed Data (ADD) approach for healthcare recommendation systems that relies on randomization, masking, and homomorphic encryption techniques with little computational costs [86]. According to the authors, the main innovation of this research is using a privacy-preserving collaborative filtering technique for generating health recommendations based on the data distribution among several parties. Three protocols are proposed: Protocol one calculates the similarity between items, Protocol two determines the item vectors' length, and Protocol three creates predictions and analysis. The findings were evaluated using different parameters, and the results obtained showed that the accuracy and coverage of the scheme outperformed other competing methods, especially when multiple parties collaborated. The benefits of this study include improved security and no loss of accuracy due to the implementation of privacy measures. The researchers were also successful in reducing the computational time of the off-line model generation process. One of the limitations of this research is the requirement for synchronization between computations performed by multiple parties to ensure proper computation.

Han et al. developed a hybrid recommender system to streamline the appointment process for primary care physicians [87]. They used large data collection to understand patients' beliefs in the family doctor. In addition, they also blended the patient and doctor metadata to observed the pattern. The system offers personalized doctor recommendations and more accurate results than the collaborative filtering technique and heuristic baselines.

Hybrid Collaborative Filtering Model for Healthcare (HCFMH) improves search for physicians by outperforming baseline approaches on the dataset with sparse data [88]. The model identifies items proactively and provides reminders to clinicians about missed information. However, the researchers face a "cold-start" problem, as missing patient encounter data prevents the generation of recommendations.

Rustam et al. proposed an automatic diagnoses diseases system that could recommend preventative measures based on patient symptoms [51,89]. The system uses machine learning algorithms, categorical data conversion, and speech data extraction. It uses a microphone to record patient voice data and assesses the performance of speech recognizers. The accuracy of the method is assessed using F1-score, recall, precision, and accuracy. Their analysis indicated that text data is often more accurate than categorical data. It was also observed that accuracy improved when classifiers accessed a large feature vector.

Shambour et al. [90] presented a hybrid system based on content-based and collaborative filtering to address the challenge of finding the best-suited doctors for patients amidst the vast amount of available healthcare information. The proposed system incorporates a multi-criteria collaborative filtering

approach to help patients accurately identify doctors that align with their preferences. It utilizes multi-criteria decision-making, doctor reputation scores, and doctors' content information to improve recommendation quality and mitigate the impact of data sparsity. Their evaluation results demonstrate the effectiveness of the proposed approach with regards to predictive accuracy and coverage under extreme levels of sparsity.

In another work, Shambour et al. [91] proposed a medicine recommendation system called Hybrid Semantic-based Multi-Criteria Collaborative Filtering (HSMCCF) to help patients find appropriate medications based on their medical conditions. The system uses a dataset of patient ratings on medicines from WebMD. It contains two main modules: a semantic filtering module that groups medicines by medical condition, and a multi-criteria filtering module that considers patient preferences across multiple rating criteria. The semantic module addresses data sparsity, while the multi-criteria module improves recommendation accuracy. A medicine reputation score is also used to expand the pool of similar medicines considered. Experiments show the HSMCCF approach improves prediction accuracy and coverage compared to benchmark methods, especially on sparse datasets and for new medicines with few ratings.

Roy et al. [92] introduced health recommender systems (HRS) which is personalised healthcare advice based on one lifestyle choices, medical histories, and other characteristics. There is a description of several forms of HRS, such as diagnosis decision support systems, health status prediction systems, nutrition and physical activity recommendations, and healthcare professional recommendation systems. The paper then surveys the current literature on these different HRS, describing techniques, features, applications and challenges of existing work. It highlights areas for further research, such as incorporating more diverse data sources, improving personalization and algorithm transparency, and conducting rigorous evaluations of HRS impact on patient outcomes. In conclusion, the survey provides an overview of HRS research trends and guidance to improve health recommender systems.

Ooi et al. [93] outlined the framework for the HRS, encompassing various recommender system techniques, datasets used, and evaluation metrics employed in the healthcare domain. The paper emphasizes the significance of accurate medical recommendations and the potential of recommender systems to enhance patient care and decision-making processes. It also presents insights into the theoretical framework, dataset, data cleaning process, recommender engine, and user interface, offering a comprehensive overview of the entire system's development and evaluation.

Navin et al. [94] proposed a knowledge-based recommender system model for disease diagnosis and treatment recommendations using adaptive fuzzy logic systems. It presents an architecture consisting of multiple parallel "fuzzy blocks" which act as fuzzy rule-based classifiers for sub-medical conditions. A

knowledge-based combiner segment combines the outputs of these fuzzy blocks using a rule base to provide holistic diagnoses and treatment recommendations. The system is configured and evaluated for basic lung disease diagnosis using a sample patient dataset. The results show good agreement with expert evaluations.

Table 3 depicts the summary of related works reviewed.

**TABLE 3. Summary of related works.**

Reference	Findings	Evaluation
[85], 2017 Dataset: The data used is from Yelp, a service that collects reviews from the public. <a href="http://www.yelp.com/dataset-challenge">http://www.yelp.com/dataset-challenge</a>	Proposed iDoctor, a specialized and personalized system for making doctor recommendations. It can do text sentiment analysis, topic modelling, matrix factorization, and other techniques on crowdsourced reviews of healthcare.	RMSE is far lower than that of other models, demonstrating the accuracy of iDoctor's doctor recommendations.
[86], 2018 The healthcare simulation dataset includes discrete evaluations from 1 to 5 for 500 clinicians and 10,000 patients.	Proposed several party ADD methods based on low-cost homomorphic, masking, and randomization encryption approaches for healthcare recommendation systems.	The planned work's correctness is determined using MAE.
[87], 2018 Dataset: European health care provider	Proposed a collaborative filtering recommender system to match patients to doctors.	Compare model performance with a heuristic baseline model.
[88], 2020 Physician searches at Eskenazi Health in Marion County, Indiana, USA, logged from April 2013 to May 2016 comprise the data used in the research.	Suggested search terms to physicians, a methodology known as the Hybrid Collaborative Filtering Model for Healthcare (HCFMH) was developed. With the help of this research, practitioners will be given helpful reminders regarding information that may have been indications they may have overlooked.	Performance metric, hit rate at k (HR@k) is employed.
[89], 2022 The dataset for the current study was taken from Kaggle. The dataset includes separate files for symptoms and safety measures.	Introduced an automated healthcare system that can successfully take the place of a physician at the first stage of diagnosis and contribute to time savings by advising the appropriate measures.	Performance metrics such as accuracy, precision, and F1 score

[90], 2023 Dataset: RateMDs Ratemds.com	Used a doctor's reputation score and the substance of their medical practice as multiple decision-making factors to improve the quality of their suggestions and lessen the impact of data sparsity.	Performance metrics such as prediction coverage, the RMSE, and the MAE.
[91], 2023 Dataset: WebMD	Medicine recommendation system called Hybrid Semantic-based Multi-Criteria Collaborative Filtering (HSMCCF) to help patients find appropriate medications based on their medical conditions.	Performance evaluation based on accuracy,
[92], 2023 Dataset: Research paper since year 2019	The survey provided an overview of HRS research trends and guidance to improve health recommender systems.	Various evaluation metrics were surveyed.
[93], 2023 Dataset: "mtsamples.csv" dataset, taken from Kaggle.com	Proposed the framework for the HRS, encompassing various recommender system techniques, datasets used, and evaluation metrics employed in the healthcare domain	Similarity score, word count
[94], 2024 Dataset: Proprietary dataset from Hospital	Disease diagnosis and treatment recommendations using adaptive fuzzy logic, which utilizes rule base to provide holistic diagnoses and treatment recommendations	Expert evaluation

#### IV. CONCLUSION AND FUTURE WORK

In conclusion, HRS are vital tools in modern healthcare. They streamline treatment processes, improve patient outcomes, and optimize resource allocation. By providing personalized recommendations based on vast data, they empower patients to take control of their health and help practitioners stay updated on the latest research and treatments. In this paper, we have reviewed the recommender techniques, application of the recommender system, evaluation metrics and related works of recommender systems in healthcare domain.

Some of the future works include surveying machine learning techniques that could incorporate adaptive learning mechanisms that enable continuous improvement over time. In addition, our current review is limited to single source. As such, we could explore the integration of multi-modal data sources, including



electronic health records (EHRs), genomic data, social determinants of health, environmental factors, and even patient-reported outcomes in our future work.

#### ACKNOWLEDGMENT

The authors receive no funding supporting this research work.

#### AUTHOR CONTRIBUTIONS

Su-Cheng Haw: Conceptualization, Data Curation, Methodology, Validation, Writing – Original Draft Preparation.

Jayapradha Jayaram: Project Administration, Supervision, Writing – Review & Editing

Elham Abdulwahab Anaam: Project Administration, Supervision, Writing – Review & Editing

Heru Agus Santoso: Project Administration, Supervision, Writing – Review & Editing

#### CONFLICT OF INTERESTS

No conflict of interests were disclosed.

#### ETHICS STATEMENTS

Our publication ethics follow The Committee of Publication Ethics (COPE) guideline. <https://publicationethics.org/>

#### REFERENCES

- [1] M. Leiva, M.C.D. Budan and G.I.Simari, "Guidelines for the analysis and design of argumentation-based recommendation systems," *IEEE Intelligent Systems*, vol. 35, no. 5, pp. 28-37, 2023.  
DOI: <https://doi.org/10.1109/MIS.2020.2999569>
- [2] N. Kumar, K.H.S. Sai, V. Hordiiichuk, R. Menon, C.J. Aarthy, G.C. Saha and K. Balaji, "Harnessing the power of big data: challenges and opportunities in analytics", *Tuijin Jishu/Journal of Propulsion Technology*, vol. 44, no. 2, pp. 363-371, 2023.  
DOI: <https://doi.org/10.52783/tijpt.v44.i2.193>
- [3] D. Sharma, G.S. Aujla and R. Bajaj, "Evolution from ancient medication to human-centered Healthcare 4.0: A review on health care recommender systems", *International Journal of Communication Systems*, vol. 36, no. 12, pp. e4058, 2023.  
DOI: <https://doi.org/10.1002/dac.4058>
- [4] T.N.T. Tran, A. Felfernig, C. Trattner and A. Holzinger, "Recommender systems in the healthcare domain: state-of-the-art and research issues", *Journal of Intelligent Information Systems*, vol. 57, pp. 171–201. 2021.  
DOI: <https://doi.org/10.1007/s10844-020-00633-6>
- [5] A. Sae-Ang, S. Chairat, N. Tansuebchueasai, O. Fumaneeshoat, T. Ingviya and S. Chaichulee, "Drug recommendation from diagnosis codes: classification vs. collaborative filtering approaches", *International Journal of Environmental Research and Public Health*, vol. 20, no. 1, pp. 309, 2023.  
DOI: <https://doi.org/10.3390/ijerph20010309>
- [6] P. Popova, A. Anopova and E. Shlyakhto, "Trial protocol for the study of recommendation system DiaCompanion with personalized dietary recommendations for women with gestational diabetes mellitus (DiaCompanion I)", *Frontiers in Endocrinology*, vol. 14, pp. 1664-2392, 2023.  
DOI: <https://doi.org/10.3389/fendo.2023.1168688>
- [7] S. Gupta, P. Sharma and T. Reddy, "Deep learning and its applications in healthcare", *WSN and IoT*, CRC Press, Taylor and Francis Group, pp. 203-224, 2024.  
DOI: <https://doi.org/10.1201/9781003437079>
- [8] S.P. Rana, M. Dey, J. Prieto and S. Dudley, "Content-based health recommender systems", *Recommender system with machine learning and artificial intelligence: practical tools and applications in medical, agricultural and other industries*, Scrivener Publishing LLC, pp. 215-236, 2020.  
DOI: <https://doi.org/10.1002/9781119711582.ch11>
- [9] B.D. Deebak and F. Al-Turjman, "Covid-19 patient care: a content-based collaborative filtering using intelligent recommendation system", *International Summit Smart City 360°*, Springer International Publishing, pp. 31-44, 2020.  
DOI: [https://doi.org/10.1007/978-3-030-76063-2\\_3](https://doi.org/10.1007/978-3-030-76063-2_3)
- [10] P. Keikhosrokiani and G.M. Fye, "A hybrid recommender system for health supplement e-commerce based on customer data implicit ratings", *Multimedia Tools and Applications*, vol. 83, pp. 45315–45344, 2023.  
DOI: <https://doi.org/10.1007/s11042-023-17321-6>
- [11] S. Mohapatra and K. Anand, "A brief model overview of personalized recommendation to citizens in the health-care industry", *Recommender System with Machine Learning and Artificial Intelligence: Practical Tools and Applications in Medical, Agricultural and Other Industries*, Scrivener Publishing LLC, pp. 27-44, 2020.  
DOI: <https://doi.org/10.1002/9781119711582.ch2>
- [12] P. Khanna, S. Kumar, N. Sodhi and A. Tiwari, "Optimal drug recommender framework for medical practitioners based on consumer reviews", *Lecture Notes in Electrical Engineering*, vol. 1011, Springer Nature Singapore, pp. 479-490, 2020.  
DOI: [https://doi.org/10.1007/978-981-99-0601-7\\_37](https://doi.org/10.1007/978-981-99-0601-7_37)
- [13] L. Jacaruso, "Insights into the nutritional prevention of macular degeneration based on a comparative topic modeling approach", *PeerJ Computer Science*, vol. 10, pp. e1940, 2024.  
DOI: <https://doi.org/10.7717/peerj-cs.1940>
- [14] B.A. Yilma, C.M. Kim, G.C. Cupchik and L.A. Leiva, "Artfulpath to healing: using machine learning for visual art recommendation to prevent and reduce post-intensive care", *Proceedings of the CHI Conference on Human Factors in Computing Systems*, vol. 16, pp. 1-19, 2024.  
DOI: <https://doi.org/10.48550/arXiv.2402.15643>
- [15] Y.H. Chang, Y.T. Guo, L.C. Fu, M.J. Chiu, H.M. Chiu and H.J. Lin, "Interactive healthcare robot using attention-based question-answer retrieval and medical entity extraction models", *IEEE Journal of Biomedical and Health Informatics*, vol. 27, no. 12, pp. 6039-6050, 2023.  
DOI: <https://doi.org/10.1109/JBHI.2023.3320939>
- [16] A.S. Adishesha, L. Jakielaszek, F. Azhar, P. Zhang, V. Honavar, F. Ma and S.X. Huang, "Forecasting user interests through topic tag predictions in online health communities", *IEEE Journal of Biomedical and Health Informatics*, vol. 27, no. 7, pp. 3645-3656, 2023.  
DOI: <https://doi.org/10.1109/JBHI.2023.3271580>
- [17] B. Athira, S.M. Idicula, J. Jones and A. Kulanthaivel, "An answer recommendation framework for an online cancer community forum", *Multimedia Tools and Applications*, vol. 83, no.1, pp. 173-199, 2024.  
DOI: <https://doi.org/10.1007/s11042-023-15477-9>
- [18] A.D. Loiatile, D. Veneto, A. Agrimi, G. Semeraro and N. Amoroso, "An AI-based approach for the improvement of university technology transfer processes in healthcare, information systems and technologies," *Lecture Notes in Networks and Systems*, Springer, Cham, vol. 802, pp 311–320, 2023.  
DOI: [https://doi.org/10.1007/978-3-031-45651-0\\_31](https://doi.org/10.1007/978-3-031-45651-0_31)
- [19] R. Oruche, V. Gundlapalli, A.P. Biswal, P. Calyam, M.L. Alarcon, Y. Zhang, N.R. Bhamidipati, A. Malladi and H. Regunath, "Evidence-based recommender system for a covid-19 publication analytics service", *IEEE Access*, vol. 9, pp. 79400-79415, 2021.  
DOI: <https://doi.org/10.1109/ACCESS.2021.3083583>
- [20] S.R. Sripathi, N.V.S. Pradyumna, A. Dhanush and R. Subramani, "Drug recommendation system using LDA", *International Conference on Futuristic Technologies*, pp. 1-7, 2022.  
DOI: <https://doi.org/10.1109/INCOFT55651.2022.10094396>
- [21] M. Mustakim, R. Wardoyo, K. Mustofa, G.R. Rahayu and I. Rosyidah, "Latent dirichlet allocation for medical records topic

- modeling: systematic literature review", *International Conference on Informatics and Computing*, pp. 1-7, 2021.  
DOI: <https://doi.org/10.1109/ICIC54025.2021.9632993>
- [22] Sudhanshu, N.S. Punn, S.K. Sonbhadra and S. Agarwal, "Recommending best course of treatment based on similarities of prognostic markers", *International Conference on Neural Information Processing*, Springer International Publishing, pp. 393-404, 2021.  
DOI: [https://doi.org/10.1007/978-3-030-92270-2\\_34](https://doi.org/10.1007/978-3-030-92270-2_34)
- [23] N.V. Rahul, S.N.I.S Geethika, S.C. Aishwarya, V. Revanth and S. Fathimabi, "Indian health network—a patient recommender system for the Indian community with health records", *Lecture Notes in Networks and Systems*, vol. 446, pp 313–325, 2021.  
DOI: [https://doi.org/10.1007/978-981-19-1559-8\\_32](https://doi.org/10.1007/978-981-19-1559-8_32)
- [24] R. Bateja, S.K. Dubey and A. Bhatt, "Prescription based recommender system for diabetic patients using efficient map reduce", *Engineering Journal*, vol. 26, no. 10, pp. 85-98, 2022.  
DOI: <https://doi.org/10.4186/ej.2022.26.10.85>
- [25] S. Shah, V. Naik, D. Mukhopadhyay and S. Roy, "Generic medicine recommender system with incorporated user feedback", *International Internet of Things Conference*, Springer Nature Switzerland, pp. 64-73, 2023.  
DOI: [https://doi.org/10.1007/978-3-031-45882-8\\_5](https://doi.org/10.1007/978-3-031-45882-8_5)
- [26] A. Yashudas, D. Gupta, G.C. Prashant, A. Dua, D. AlQahtani and A.S.K. Reddy, "DEEP-CARDIO: recommendation system for cardiovascular disease prediction using IOT network", *IEEE Sensors Journal*, vol. 24, no. 9, pp. 14539-14547, 2024.  
DOI: <https://doi.org/10.1109/JSEN.2024.3373429>
- [27] F. Zhang and X. Li, "Knowledge-enhanced online doctor recommendation framework based on knowledge graph and joint learning", *Information Sciences*, vol. 662, pp. 120268, 2024.  
DOI: <https://doi.org/10.1016/j.ins.2024.120268>
- [28] A. Rehman, N. Aslam, K. Abid and M. Fuzail, "The impact of COVID-19 on e-learning: context-based sentiment analysis discourse using text mining", *VAWKUM Transactions on Computer Sciences*, vol. 11, no. 1, pp. 184-203, 2023.  
DOI: <https://doi.org/10.21015/vtcs.v11i1.1489>
- [29] A.I. Alaie, U. Farooq, W.A. Bhat, S.S. Khurana and P. Singh, "An empirical study on sentimental drug review analysis using lexicon and machine learning-based techniques", *SV Computer Science*, vol. 5, no. 1, pp. 1-14, 2023.  
DOI: <https://doi.org/10.1007/s42979-023-02384-x>
- [30] Y.L. Sukestiyarno, H.A. Sapolo and H. Sofyan, "Application of Recommendation System on E-Learning Platform Using Content-Based Filtering with Jaccard Similarity and Cosine Similarity Algorithms", *Preprints 2023*, pp. 2023061672, 2023.  
DOI: <https://doi.org/10.20944/preprints202306.1672.v1>
- [31] T. Iqbal, M. Masud, B. Amin, C. Feely, M. Faherty, T. Jones, M. Tierney, A. Shahzad and P. Vazquez, "Towards integration of artificial intelligence into medical devices as a real-time recommender system for personalised healthcare: state-of-the-art and future prospects", *Health Sciences Review*, vol. 10, pp. 100150, 2024.  
DOI: <https://doi.org/10.1016/j.hsr.2024.100150>
- [32] L.V. Nguyen, Q.T. Vo and T.H. Nguyen, "Adaptive KNN-based extended collaborative filtering recommendation services", *Big Data and Cognitive Computing*, vol. 7, no. 2, pp. 1-13, 2023.  
DOI: <https://doi.org/10.3390/bdcc7020106>
- [33] D. Gautam, A. Dixit, S.B. Goyal, C. Verma and M. Kumar, "A novel approach to enhance the quality of health care recommender system using fuzzy-genetic approach", *Journal of Intelligent & Fuzzy Systems*, vol. 45, no. 4, pp. 5509-5522, 2023.  
DOI: <https://doi.org/10.3233/JIFS-224257>
- [34] M. Kuanr and P. Mohapatra, "Outranking relations based multi-criteria recommender system for analysis of health risk using multi-objective feature selection approach", *Data & Knowledge Engineering*, vol. 145, pp. 102144, 2023.  
DOI: <https://doi.org/10.1016/j.datak.2023.102144>
- [35] A. Hessane, A. El Youssefi, Y. Farhaoui, B. Aghoutane, N.A. Ali and A. Malik, "Healthcare providers recommender system based on collaborative filtering techniques", *Machine Learning and Deep Learning in Medical Data Analytics and Healthcare Applications*, CRC Press, pp. 261-274, 2022. URL: <https://www.taylorfrancis.com/chapters/edit/10.1201/9781003226147-15/healthcare-providers-recommender-system-based-collaborative-filtering-techniques-abdelaziz-hessane-ahmed-el-youssefi-yousef-farhaoui-badraddine-aghoutane-noureddine-ait-ali-ayasha-malik> (accessed 22 July, 2024).
- [36] S.P. Erdeniz, M. Schrepf, D. Kramer and A. Felfernig, "A comparative study: classification vs. matrix factorization for therapeutics recommendation", *International Symposium on Methodologies for Intelligent Systems*, Springer International Publishing, pp. 467-476, 2022.  
DOI: [https://doi.org/10.1007/978-3-031-16564-1\\_45](https://doi.org/10.1007/978-3-031-16564-1_45)
- [37] A. Alferaidi, K. Yadav, S. Yasmeen, Y. Alharbi, W. Viriyasitavat, G. Dhiman and A. Kaur, "Node multi-attribute network community healthcare detection based on graphical matrix factorization", *Journal of Circuits, Systems and Computers*, vol. 33, no. 05, pp. 2450080, 2023.  
DOI: <https://doi.org/10.1142/S0218126624500804>
- [38] N.M. Sinchana, K.K.R. Prasanna and B.J. Santhosh, "Model-based filtering techniques for recommendation systems in healthcare domain", *International Conference on I-SMAC (IoT in Social, Mobile, Analytics and Cloud)(I-SMAC)*, pp. 978-983, 2023.  
DOI: <https://doi.org/10.1109/I-SMAC58438.2023.10290568>
- [39] S. Shao, Y. Xia, K. Bai and X. Zhou, "A quasi-newton matrix factorization-based model for recommendation", *International Journal of Web Services Research*, vol. 20, no. 1, pp. 1-15, 2023.  
DOI: <https://doi.org/10.4018/IJWSR.334703>
- [40] Z. Movafegh and A. Rezapour, "Improving collaborative recommender system using hybrid clustering and optimized singular value decomposition", *Engineering Applications of Artificial Intelligence*, vol. 126, pp. 107109, 2023.  
DOI: <http://dx.doi.org/10.1016/j.engappai.2023.107109>
- [41] P. Symeonidis, G. Manitaras and M. Zanker, "Accurate and safe drug recommendations based on singular value decomposition", *IEEE 36th international symposium on computer-based medical systems*, pp. 163-168, 2023.  
DOI: <https://doi.org/10.1109/CBMS58004.2023.00210>
- [42] X. Deng and F. Huangfu, "Collaborative variational deep learning for healthcare recommendation", *IEEE Access*, vol. 7, pp. 55679-55688, 2019.  
DOI: <https://doi.org/10.1109/ACCESS.2019.2913468>
- [43] S. Khan, V. Ch, K. Sekaran, K. Joshi, C. K. Roy and M. Tiwari, "Incorporating deep learning methodologies into the creation of healthcare systems," *International Conference on Artificial Intelligence and Smart Communication*, pp. 994-998, 2023.  
DOI: <https://doi.org/10.1109/AISC56616.2023.10085651>
- [44] J.G.D. Ochoa, O. Csiszar and T. Schimper, "Medical recommender systems based on continuous-valued logic and multi-criteria decision operators, using interpretable neural networks", *BMC Medical Informatics and Decision Making*, vol. 21, pp. 186, 2021.  
DOI: <https://doi.org/10.1186/s12911-021-01553-3>
- [45] S. Dongre and J. Agrawal, "Deep-learning-based drug recommendation and ADR detection healthcare model on social media," *IEEE Transactions on Computational Social Systems*, vol. 10, no. 4, pp. 1791-1799, 2023.  
DOI: <https://doi.org/10.1109/TCSS.2022.3231701>
- [46] Q. Chen, X. Liu, M. Liao, Y. He and F. Mu, "Medical quality assessment and professionalized recommendations based on deep learning", *ICIC Express Letters*, vol. 14, no. 4, pp. 369-377, 2020.  
DOI: <https://doi.org/10.24507/icicel.14.04.369>
- [47] A.K. Azmi, N. Abdullah and N.A. Emran, "A collaborative filtering recommender system model for recommending intervention to improve elderly well-being", *International Journal of Advanced Computer Science and Applications*, vol. 10, no. 6, pp. 131-138, 2019.  
DOI: <https://doi.org/10.14569/IJACSA.2019.0100619>
- [48] A. Hessane, A. El Youssefi, Y. Farhaoui, B. Aghoutane, N.A. Ali and A. Malik, "Healthcare providers recommender system based on collaborative filtering techniques", *Machine Learning and Deep Learning in Medical Data Analytics and Healthcare Applications*, CRC Press, pp. 261-274, 2022.  
DOI: <https://dx.doi.org/10.1201/9781003226147-15>
- [49] R. Lewis, C. Ferguson, C. Wilks, N. Jones and R.W. Picard, "Can a recommender system support treatment personalisation in digital mental health therapy? A quantitative feasibility assessment using data from a behavioural activation therapy app," *Conference on Human Factors in Computing Systems*, pp. 1-8, 2022.  
DOI: <https://doi.org/10.1145/3491101.3519840>



- [50] L.A. Shubhashree, S. Chaudhari and R. Apama, "A nutrition-based smart recipe recommender for healthy living", *IEEE 3rd Global Conference for Advancement in Technology*, pp. 1-6, 2022.  
DOI: <https://doi.org/10.1109/GCAT55367.2022.9971930>
- [51] . Rustam, Z. Imtiaz, A. Mehmood, V. Rupapara, G.S. Choi, S. Din and I. Ashraf, "Automated disease diagnosis and precaution recommender system using supervised machine learning", *Multimedia Tools Application*, vol. 81, no. 22, pp. 31929-31952, 2022.  
DOI: <https://doi.org/10.1007/s11042-022-12897-x>
- [52] P.S. More, B.S. Saini and R.K. Sharma, "AI-based diagnostic test prediction-an effective way to handle the new normal era in Healthcare", *International Conference on Contemporary Computing and Informatics*, vol. 6, pp. 1255-1264, 2023.  
DOI: <https://doi.org/10.1109/IC3I59117.2023.10397808>
- [53] Y.S. Chang, M. Han, B. Jeon, J.C. Kim and N. Park, "An neural collaborative filtering (NCF) based recommender system for personalized rehabilitation exercises", *International Conference on Information and Communication Technology Convergence*, pp. 1292-1297, 2023.  
DOI: <https://doi.org/10.1109/ICTC58733.2023.10393615>
- [54] I. Mazlan, N. Abdullah and N. Ahmad, "Exploring the impact of hybrid recommender systems on personalized mental health recommendations", *International Journal of Advanced Computer Science and Applications*, vol. 14, no. 6, pp. 935-944, 2023.  
DOI: <https://doi.org/10.14569/IJACSA.2023.0140699>
- [55] S. Meng, S. Fan, Q. Li, X. Wang, J. Zhang, X. Xu, L. Qi and A.Z.A. Bhuiyan, "Privacy-aware factorization-based hybrid recommendation method for healthcare services," *IEEE Transactions on Industrial Informatics*, vol. 18, no. 8, pp. 5637-5647, 2022.  
DOI: <https://doi.org/10.1109/TII.2022.3143103>
- [56] M. Sumaiya, S.K. Shukla, K. Sreenivasulu, A. Gehlot, F.D.C.D. Sales and R. Ushasree, "An effective hybrid recommender system for cardiovascular illness based on IoT", *IEEE Uttar Pradesh Section International Conference on Electrical, Electronics and Computer Engineering*, pp. 446-451, 2023.  
DOI: <https://doi.org/10.1109/UPCON59197.2023.10434564>
- [57] W. Lu and Y. Zhai, "Self-adaptive telemedicine specialist recommendation considering specialist activity and patient feedback", *International Journal of Environmental Research and Public Health*, vol. 19, no. 9, pp. 5594, 2022.  
DOI: <https://doi.org/10.3390/ijerph19095594>
- [58] Z. Hamane, A. Samih and A. Fennan, "HealthPathFinder: navigating the healthcare knowledge graph with neural attention for personalized health recommendations", *Lecture Notes in Networks and Systems Innovations in Smart Cities Applications*, vol. 7, pp. 429-446, 2024.  
DOI: [https://doi.org/10.1007/978-3-031-53824-7\\_40](https://doi.org/10.1007/978-3-031-53824-7_40)
- [59] B. Tian, Y. Zhang, X. Chen, C. Xing and C. Li, "DRGAN: a gan-based framework for doctor recommendation in chinese online QA communities", *Lecture Notes in Computer Science*, Springer, vol. 11448, 2019.  
DOI: [https://doi.org/10.1007/978-3-030-18590-9\\_63](https://doi.org/10.1007/978-3-030-18590-9_63)
- [60] M.K. Hauglid and T. Mahler, "Doctor Chatbot: The EU's regulatory prescription for generative medical AI", *Oslo Law Review*, pp. 1-23, 2023.  
DOI: <https://doi.org/10.54648/cola2022005>
- [61] K.B. Ooi, G.W.H. Tan, M. Al-Emran, M.A. Al-Sharafi, A. Capatina, A. Chakraborty and L.W. Wong, "The potential of generative artificial intelligence across disciplines: Perspectives and future directions", *Journal of Computer Information Systems*, pp. 1-32, 2023.  
DOI: <https://doi.org/10.1080/08874417.2023.2261010>
- [62] A. Beheshti, "Empowering generative ai with knowledge base 4.0: Towards linking analytical, cognitive, and generative intelligence", *IEEE International Conference on Web Services*, pp. 763-771, 2023.  
DOI: <https://doi.org/10.1109/ICWS60048.2023.00103>
- [63] W. Wang, X. Lin, F. Feng, X. He and T.S. Chua, "Generative recommendation: towards next-generation recommender paradigm", *arXiv preprint*, 2023.  
DOI: <https://doi.org/10.48550/arXiv.2304.03516>
- [64] S.K. Babu, M. Chetiah and S.V. Mammen, "Recommender-based user guidance framework", *IEEE International Conference on Artificial Intelligence and eXtended and Virtual Reality*, pp. 275-280, 2023.  
DOI: <https://doi.org/10.1109/AIXVR59861.2024.00046>
- [65] A.R.F. AlSamhori, J.F. AlSamhori and A.F. AlSamhori, "ChatGPT role in a medical survey", *High Yield Medical Reviews*, vol. 1, no. 2, pp. 1-11, 2023.  
DOI: <https://doi.org/10.59707/hymrTFFP5435>
- [66] F. Kadri, A. Dairi, F. Harrou and Y. Sun, "Towards accurate prediction of patient length of stay at emergency department: a GAN-driven deep learning framework", *Journal of Ambient Intelligence and Humanized Computing*, vol. 14, no. 9, pp. 11481-11495, 2023.  
DOI: <https://doi.org/10.1007/s12652-022-03717-z>
- [67] J. Zhang, Y. Lv, J. Hou, C. Zhang, X. Yua, Y. Wang, Y. Wang, T. Yang, X. Su, Z. Ye and L. Li, "Machine learning for post-acute pancreatitis diabetes mellitus prediction and personalized treatment recommendations", *Scientific Reports*, vol. 13, no.1, pp. 4857, 2023.  
DOI: <https://doi.org/10.1038/s41598-023-31947-4>
- [68] L. Shahmoradi, R. Safdari, M.M. Mirhosseini and S. Rezayi, "Development and evaluation of a clinical decision support system for early diagnosis of acute appendicitis", *Scientific Reports*, vol. 13, no. 1, pp. 19703, 2023.  
DOI: <https://doi.org/10.1038/s41598-023-46721-9>
- [69] M. Fernandes, S.M. Vieira, F. Leite, C. Palos, S. Finkelstein and J.M. Sousa, "Clinical decision support systems for triage in the emergency department using intelligent systems: a review", *Artificial Intelligence in Medicine*, vol. 102, pp. 101762, 2020.  
DOI: <https://doi.org/10.1016/j.artmed.2019.101762>
- [70] P.M. Reehan, N. Nikhilesh, R. Revanth, V.V. Chandra and S.B. Suvanam, "Disease prediction and medicine recommendation system", *AIP Conference Proceedings*, vol. 2742, no. 1, pp. 2742, 2024.  
DOI: <https://doi.org/10.1063/5.0184521>
- [71] S.C. Christopoulou, "Machine learning models and technologies for evidence-based telehealth and smart care: a review", *BioMedInformatics*, vol. 4, no. 1, pp. 754-779, 2024.  
DOI: <https://doi.org/10.3390/biomedinformatics4010042>
- [72] S. Aminabee, "The future of healthcare and patient-centric care: digital innovations, trends, and predictions", *Emerging Technologies for Health Literacy and Medical Practice*, IGI Global, pp. 240-262, 2024.  
DOI: <https://doi.org/10.4018/979-8-3693-1214-8.ch012>
- [73] S.A. Butt, M. Naseer, A. Ali, A. Khalid, T. Jamal and S. Naz, "Remote mobile health monitoring frameworks and mobile applications: Taxonomy, open challenges, motivation, and recommendations", *Engineering Applications of Artificial Intelligence*, vol. 133, pp. 108233, 2024.  
DOI: <https://doi.org/10.1016/j.engappai.2024.108233>
- [74] N. Villafuerte, S. Manzano, P. Ayala and M.V. Garcia, "Artificial intelligence in virtual telemedicine triage: a respiratory infection diagnosis tool with electronic measuring device", *Future Internet*, vol. 15, no.7, pp. 227, 2023.  
DOI: <https://doi.org/10.3390/fi15070227>
- [75] P. Howell, A. Aryal and C. Wu, "Web-based patient recommender systems for preventive care: protocol for empirical research propositions", *JMIR Research Protocols*, vol. 12, no.1, pp. e43316, 2023.  
DOI: <https://doi.org/10.2196/43316>
- [76] A. Alslaity and T. Tran, "ComPer: a comprehensive performance evaluation method for recommender systems", *International Journal of Information Technology and Computer Science*, vol. 11, no. 12, pp. 1-18, 2019.  
DOI: <https://doi.org/10.5815/ijitcs.2019.12.01>
- [77] G. Sood and N. Raheja, "Performance comparison of artificial intelligence-based recommendation systems based on healthcare dataset", *International Conference on Futuristic Technologies*, pp. 1-6, 2022.  
DOI: <https://doi.org/10.1109/INCOFT55651.2022.10094373>
- [78] Y. Cai, F. Yu, M. Kumar, R. Gladney and J. Mostafa, "Health recommender systems development, usage, and evaluation from 2010 to 2022: a scoping review", *International Journal of Environmental Research and Public Health*, vol. 19, no. 22, pp. 15115, 2022.  
DOI: <https://doi.org/10.3390/ijerph192215115>
- [79] C. Bauer, E. Zangerle and A. Said, "Exploring the landscape of recommender systems evaluation: practices and perspectives", *ACM Transactions on Recommender Systems*, vol. 2, no. 1, pp. 1-31, 2024.  
DOI: <https://doi.org/10.1145/3629170>

- [80] E. Slade, S. Rennick-Egglestone, F. Ng, Y. Kotera, J. Llewellyn-Beardsley, C. Newby and M. Slade, "The implementation of recommender systems for mental health recovery narratives: evaluation of use and performance", *JMIR Mental Health*, vol. 11, no. 1, pp. e45754, 2024.  
DOI: <https://doi.org/10.2196/45754>
- [81] J. Paz-Ruza, A. Alonso-Betanzos, B. Guijarro-Berdinas, B. Cancela and C. Eiras-Franco, "Beyond RMSE and MAE: introducing EAUC to unmask hidden bias and unfairness in dyadic regression models". *arXiv preprint*, 2024.  
DOI: <https://doi.org/10.48550/arXiv.2401.10690>
- [82] T. Tu, J. Zhang, Y. Wang, H. Jin and M.W. He, "MULABS: multi-task learning with attention-based scoring for click-through rate prediction on sparse data in healthcare real-world scenarios", *International Conference on Bioinformatics and Biomedicine*, pp. 3890-3892. 2022.  
DOI: <https://doi.org/10.1109/BIBM55620.2022.9995650>
- [83] F. Rajabi and J.S. He, "Click-Through Rate Prediction Using Graph Neural Networks and Online Learning". *ArXiv preprint*, 2021.  
DOI: <https://doi.org/10.48550/arXiv.2105.03811>
- [84] S. Lyu, Q. Chen, T. Zhuang and J. Ge, "Entire Space Learning Framework: Unbias Conversion Rate Prediction in Full Stages of Recommender System", *ArXiv preprint*, 2023.  
DOI: <https://doi.org/10.48550/arXiv.2303.00276>
- [85] Y. Zhang, M. Chen, D. Huang, D. Wu and Y. Li, "iDoctor: personalized and professionalized medical recommendations based on hybrid matrix factorization", *Future Generation Computer Systems*, vol. 66, pp. 30–35, 2017.  
DOI: <https://doi.org/10.1016/j.future.2015.12.001>
- [86] H. Kaur, N. Kumar and S. Batra, "An efficient multi-party scheme for privacy preserving collaborative filtering for Healthcare Recommender System", *Future Generation Computer Systems*, vol. 86, pp. 297-307, 2018.  
DOI: <https://doi.org/10.1016/j.future.2018.03.017>
- [87] Q. Han, M. Ji, I. Martinez De Rituerto De Troya, M. Gaur, and L. Zejinilovic, "A hybrid recommender system for patient-doctor matchmaking in primary care," *International Conference on Data Science and Advanced Analytics*, pp. 481-490, 2018.  
DOI: <https://doi.org/10.1109/DSAA.2018.00062>
- [88] Z. Ren, B. Peng, T.K. Schleyer and X. Ning, "Hybrid collaborative filtering methods for recommending search terms to clinicians", *Journal of Biomedical Informatics*, vol. 113, pp. 103635, 2020.  
DOI: <https://doi.org/10.1016/j.jbi.2020.103635>
- [89] P. Gupta, F. Rustam, K. Kanwal, W. Aljedaani, S. Alfarhood, M. Safran and I. Ashraf, "Detecting thyroid disease using optimized machine learning model based on differential evolution", *International Journal of Computational Intelligence Systems*, vol. 17, no. 3, pp. 1-19, 2024.  
DOI: <https://doi.org/10.1007/s44196-023-00388-2>
- [90] Q.Y. Shambour, M.M. Al-Zyouid, A.H. Hussein and Q.M. Kharma, "A doctor recommender system based on collaborative and content filtering," *International Journal of Electrical and Computer Engineering*, vol. 13, no. 1, pp. 884-893, 2023.  
DOI: <http://doi.org/10.11591/ijece.v13i1.pp884-893>
- [91] Q.Y. Shambour, M.M. Al-Zyouid, A.A. Abu-Shareha and M. Abualhaj, "Medicine recommender system based on semantic and multi-criteria filtering", *Interdisciplinary Journal of Information, Knowledge, and Management*, vol. 18, pp. 435-457, 2023.  
DOI: <https://doi.org/10.28945/5172>
- [92] D. Roy and M. Dutta, "A survey on personalized health recommender systems for diverse healthcare applications", *International Conference on Computing and Communication Systems*, pp. 1-9, 2023.  
DOI: <https://doi.org/10.1109/I3CS58314.2023.10127238>
- [93] K.N. Ooi, S.C. Haw and K.W. Ng, "A healthcare recommender System Framework", *International Journal on Advanced Science, Engineering & Information*, vol. 13, no. 6, pp. 2282-2293. 2023.  
DOI: <https://doi.org/10.18517/ijaseit.13.6.19049>
- [94] K. Navin and M.B.M. Krishnan, "Knowledge based recommender system for disease diagnostic and treatment using adaptive fuzzy-blocks", *KSII Transactions on Internet and Information Systems*, vol. 18, no. 2, pp. 284-310, 2024.  
DOI: <https://doi.org/10.3837/tiis.2024.02.002>