
Journal of Informatics and Web Engineering

Vol. 5 No. 3 (October 2026)

eISSN: 2821-370X

Intelligent Telemedicine Systems: Machine Learning for Remote Diagnosis and Patient Management

Oras Baker^{1**}, Kasthuri Subaramaniam^{2*}, Asiah Lokman³

¹Faculty of Computing and Emerging Technology, Ravensbourne University London, London SE10 0EW, United Kingdom

²Department of Decision Science, Faculty of Business and Economics, Universiti Malaya, 50603 Kuala Lumpur, Malaysia

³School of Computing & Artificial Intelligence, Malaysia University of Science and Technology, 47810 Petaling Jaya, Selangor, Malaysia

*corresponding author: (s_kasthuri@um.edu.my; ORCID: 0000-0003-0704-923X)

**corresponding author: (O.alhassani@rave.ac.uk; ORCID: 0000-0002-0958-4861)

Abstract - Telemedicine has experienced significant evolution in the past 10 years from a communication-driven health service to an intelligent, data-driven environment driven by AI (artificial intelligence), ML (machine learning), IoMT (Internet of Medical Things) and cloud-edge computing. This development has been further advanced through ongoing global health challenges that have seen an ageing population, rising burden of chronic, multi-morbid conditions, healthcare specialist shortage, soaring cost of healthcare and major disruptions like the COVID-19 pandemic. Modern telehealth services are now integrating more machine learning algorithms for remote diagnosis, real-time monitoring the patient, predictive risk stratification and proactive treatment. This paper offers a comprehensive academic overview of intelligent telemedicine systems using machine learning for remote diagnosis and patient management. It synthesises and reviews recent literature on image-based diagnostics, physiological time-series modelling, NLP algorithms used to interpret symptoms, and multimodal data fusion models. An integrated system architecture is proposed and presented to illustrate how IoMT devices, data collection pipelines, preprocessing layers, machine learning inbound engines, and clinician decision tools are interlinked in the digital telemedicine landscape. We evaluated a proof-of-concept machine learning workflow for short-term patient deterioration prediction, relying on synthetic IoMT-style patient datasets to demonstrate real-world feasibility and clinical relevance. Apart from technical performance, the paper also describes the challenges of data quality, interoperability, algorithmic bias, explainability, cybersecurity, regulatory compliance, and integration into clinical workflows. Ethical questions, including trust in intelligent healthcare, responsibility, patients' autonomy, and fair treatment, are raised. Finally, opportunities for future research are mentioned, including digital twins, federated learning, explainable AI, autonomous IoMT ecosystems, and emotionally intelligent telemedicine platforms to guide researchers, clinicians, systems designers, and policy makers on the evolution of telemedicine in a way that is intelligent, proactive and just in health care.

Keywords—Telemedicine, Machine Learning, Remote Diagnosis, Digital Health, Predictive Analytics

Received: 5 February 2026; Accepted: 29 June 2026; Published: 16 October 2026

This is an open access article under the [CC BY-NC-ND 4.0](#) license.



1. INTRODUCTION

Telemedicine is no longer an alternative to healthcare but has become an integral part of today's system. The early telemedicine programs focused primarily on enabling remote communication between patients and their healthcare providers with video conferencing, phone check-ins, and asynchronous communication of medical pictures. While these technologies made care accessible to more people, particularly in rural and underserved areas, they were largely clinician-specific, reactive and did far less to provide analytical data support or automation. Over the past decade, AI and machine learning have evolved quite a bit and have completely disrupted telemedicine. The current telemedicine system is an amalgam of dozens of intelligent techniques that integrate data-based systems with data-aided systems. It includes automatic diagnosis, monitoring, early warning generation, and treatment recommendation personalised with data for each user. As technology continues to evolve in this era it parallels healthcare to a future of prevention, prediction, personalised care and active participation.

This transition has been accelerated by several macro-level forces. Aging populations and increased burden from chronic diseases are prompting longer, more continuous care around the world. Chronic shortages in the health care workforce and insufficient specialisation have added pressure on mainstream care models. The COVID-19 pandemic was a tremendous transition, prompting the quick emergence of telemedicine to provide seamless care with decreased interactions [1]. For triage, remote monitoring and population management, at scale, machine learning embedded technology-rich telemedicine platforms were beneficial. These results suggest that ML-augmented telemedicine may offer advantages over traditional diagnostic technologies in terms of performance and workload reduction, while also potentially supporting earlier clinician detection and intervention, and promotes a more active population of patients in a wider range of clinical domains, including dermatology, cardiology, diabetes, respiratory and mental health [2], [3], [4], [5], [6].

Several new technologies have been discovered although only a few examples of deployments in the field exist. These technical challenges from data interoperability and sensor reliability to system scalability live alongside ethical and regulatory considerations for topics like privacy, algorithmic bias, transparency and accountability. Whereas other works focus on the details of specific algorithms or specific applications, this paper presents a holistic architecture regarding IoMT devices, data pipelines, machine learning analytics, and clinician decision systems for intelligent telemedical care. This study addresses these knowledge gaps by presenting an integrated framework for intelligent telemedicine systems. The paper indeed demonstrates that machine learning technology allows remote diagnosis and patient management, describes system architectures required for a scalable implementation, and offers a realistic feasibility study through a ML-based risk prediction workflow. It discusses the limitations, ethical concerns and opportunities on the path of future studies.

2. BACKGROUND AND RELATED WORK

Telemedicine imagines global healthcare systems that are not tied down with a clinical setting, empowered by data and communication tools. The early telemedicine programs were reactive with episodic and remote consultation which lack the high analytical intelligence [7]. With the rise of mobile devices, wearables, and IoMT, data are being collected continuously in real-time, enabling fresh data-driven healthcare.

Machine learning has become one fundamental technology enabling contemporary telemedicine infrastructure. Supervised learning tools are extensively applied in disease classification, risk stratification, and outcome estimation, and unsupervised methods have been used to detect abnormalities in physiological signals [5]. Deep learning methodologies, such as convolutional neural networks, have shown good performance in image based tele-diagnostics, which incorporate classification of skin lesion, retinal disease detection, and observation of radiological images [8], [9].

Incorporation of temporal models including recurrent neural networks and long short-term memory architectures to physiological time-series data from wearable devices allows for early recognition of clinical deterioration due to temporal patterns between physiological activities or patterns or conditions. Automated symptom extraction, triage support, and conversational interfaces are easy to achieve using natural language processing methods in teleconsultation tools [6], [7]. Multimodal learning paradigms that integrate heterogeneous data sources, with examples such as images, sensor data, text, and demographic data are becoming popular to enhance robustness and clinical relevance in recent years [2], [18].

Recent investigations emphasised the importance of AI based diagnostic and predictive utility for telemedicine as a new field for telemedicine. Imaging with image focused diagnostics and forecasting approach in pandemic has made the way to early diagnosis and emerging technology has allowed us to detect conditions in real time and edge computing ecosystem has provided the immediate evaluation in real time [9]. Disease predictive models, and collaborative disease prediction paradigms, are developing and advancing control of well-being [10], [11]. Although literature reviews have been conducted for the implementation of AI for telemedicine only, one of the areas of interest in the literature are system, diagnostic, patient centered care and operational feasibility. To address these research gaps, our paper aims to be designed to synthesise these components within an academic framework from end to end.

This study therefore presents an end-to-end holistic machine learning based pipeline for telemedicine applications in regard to data preprocessing, feature engineering, model training and risk prediction. The following preprocessing steps were undertaken: 1) imputation of missing data, 2) normalisation of features, 3) outlier detection, 4) temporal alignment of physiological measurements, 5) standardisation of the training data. We extracted features from physiological and behavioral measurements that identified early clinical deterioration. We split the dataset into training and testing sets and trained our model using supervised learning. Performance was assessed with common classification measures such as accuracy, precision, recall, F1-score, and ROC-AUC. The work shows that clinically relevant predictions with interpretable models like Random Forest can be achieved with high transparency which is required in a healthcare scenario. These achievements set the work apart from other literature which emphasises unsynchronised machine learning models and overlooks system-level support for scalable telemedicine systems.

3. SYSTEM ARCHITECTURE OF INTELLIGENT TELEMEDICINE

To have intelligent telemedicine systems, they need to have robust and scalable architectures to manage heterogeneous data streams, support real-time analytics, and make secure and reliable communication possible. Current systems use layered architectures which separate data acquisition, processing, analytics, and presentation layers to improve modular design, and interoperability. At the patient interaction end, people utilise telemedicine platforms by accessing them via mobile devices, teleconsultation interfaces, wearable IoMT devices, or home monitoring equipment. Such devices harvest a wide range of data, including physiological data: pulse, oxygen saturation, temperature, behavioural cues: physical activity, sleeping, medical photographs, audio samples, or symptoms the patient reports.

The dataset acquisition and integration layer combines input from various devices and sources. This layer is responsible for preprocessing, noise removal, normalising, feature extraction, temporal alignment, and encryption. Data quality management is a vital first step towards trustworthy downstream analytics. Central to this system is a machine learning layer. In this, the models are involved in diagnostic inference, anomaly detection, risk prediction, multimodal data fusion. Inference can be carried out on edge devices, cloud servers and hybrid cloud-edge architectures, depending on latency requirements, computing capabilities and privacy concerns [12]. Outputs are then communicated to clinician-level dashboards and electronic health record systems.

Figure 1 presents the top view architecture of the intelligent telemedicine system and the reference structure for further studies.

4. MACHINE LEARNING FOR REMOTE DIAGNOSIS

Of these, remote diagnosis is one of the most powerful clinical and technologically advanced application of machine learning in telemedicine schemes [13]. Machine-learning approaches improve clinical decision making by detecting risk factors in disease early, accurately diagnosing diseases, and providing triage support in low-resource settings; this latter goal is achieved through the analysis of aggregated patient information extracted from data collected outside traditional health care environments [14]. We present synthetic IoMT-style patient dataset that is intended to model realistic remote monitoring environments. The dataset includes heart rate, oxygen saturation (SpO₂), respiratory rate, body temperature, systolic blood pressure (SBP), physical activity levels, patient age and comorbidity count variables. These variables were chosen because they are standard data available in remote patient monitoring systems. The utility of these features lies in their availability, being late and limited, for example, rural in healthcare, in the case of chronic diseases, or within public epidemics on a much larger scale [15].




Figure 1. High-Level Architecture of an Intelligent Telemedicine System

Image-based diagnosis is one of the most studied and popular opportunities for machine learning in telemedicine. Convolutional neural networks (CNNs) have demonstrated robust performance in dermatological images, wound photographs, ocular scans and radiological images obtained from patients remotely [8]. In tele-dermatology, CNN-based systems are used for non-cancerous and malignant skin lesions detection of images obtained from smartphones, which can be detected and referred by the patient at least from the beginning without coming along to the clinic. Similarly, advanced techniques used by ophthalmic telemedicine applications similarly use deep-learning algorithms to identify diabetic retinopathy and other retinal diseases based on fundus images and expand specialist diagnostic capabilities in these underserved communities. In radiology, machine learning image interpretation in this manner facilitates early screening and hierarchy in a clinic setting which improves clinician workload reduction and leads to faster diagnosis. Despite these new features, however, image-driven remote diagnosis remains a challenge with image quality variability, lighting, device heterogeneity and solid pre-processing pipelines for accurate inference through image-based remote diagnostics issues.

In addition to imaging, audio-based machine learning models have been presented as a compelling platform for remote diagnostics, particularly, in this context, of pulmonary and neurological evaluation [16]. Cough sounds, respiratory pattern and speech signal models have been trained for detection of respiratory infection, chronic obstructive pulmonary disease and early neurologic disruption [6], [17]. Audio diagnostics are attractive prospects for telemedicine use as they are low cost, easy to use and non-invasive, and also can assist normal consumer devices such as smartphones. Nonetheless, environmental noise, the variability of recording, demographic bias, and other noise may represent important factors for the subsequent design and deployment of such systems.

Time series physiological examination is also crucial for the future of machine learning-based, remote diagnostics. Wearable/hybrid IoMT devices, on the other hand, can monitor heart rate, oxygen saturation, respiration rate, temperature and physical activity in real-time. Time-series data such as described above are time-analysed by time-series machine learning models (TSMs, including recurrent neural networks and long short-term memory architectures) explicitly designed to detect divergence from patients' specific baselines of this kind, like possible or expected clinical deterioration. Time-series models offer longitudinal evaluation as opposed to making diagnoses in a snapshot, allowing for early recognition and immediate progress of the chronic disease treatment and post-acute management approach.

Natural language processing (NLP) is increasing the availability of remote diagnosis, including the ability to use automated interpretation to provide automated interpretation to patient-described symptoms, clinical narratives, and teleconsultation transcripts. NLP-derived models extract clinically important entities, severity of symptoms and context of symptoms in time, and psychosocial characteristics using free text or spoken data for integrated automatic triage and decision support [9]. In multilingual and cross-sectional telemedicine environments, NLP models can help

facilitate translation of language and dialect adaptation, thus contributing to improving accessibility and quality of diagnosis in heterogeneous patient populations by facilitating its applicability. Multimodal structures are being used and are linking various imaging data with physiological signals, audio files, textual content, demographic factors, to generate aggregated diagnostic representations, which can be interpreted for clinical significance and clinical relevance. The latter types of approaches are closer to clinical reasoning in practice where various complementary information sources contribute to our diagnosis. Still, multimodal approaches have shown significant performance improvements relative to single-modality approaches; in fact, accuracy, robustness and generalisability are often reported in empirical research [2], [19]. These models are most suitable for complicated diagnosis situations where there are multiple comorbid conditions, generic features or lack of a uniform data quality of measurement.

Table 1 provides a methodological summary of the methodologies for machine learning on remote diagnostics within telemedicine, categorised according to their data type, the model type and the diagnostic applications. Based on this table, we provide a methodological baseline for the various machine learning methods used for intelligent remote diagnostic system in telemedicine systems.

Table 1. Representative Machine Learning Techniques for Remote Diagnosis in Telemedicine

Data Modality	Machine Learning Technique	Diagnostic Application	Role in Telemedicine Context
Medical images (dermatology, radiology, ophthalmology)	Convolutional Neural Networks (CNNs)	Skin lesion classification, wound assessment, diabetic retinopathy detection, radiological screening	Enables automated image interpretation from patient-submitted images, supports early screening and prioritisation, extends specialist diagnostic capabilities to remote and underserved regions
Audio signals (cough, breathing, speech)	Deep Neural Networks, CNNs, Spectrogram-based models	Respiratory disease detection, neurological assessment, speech impairment analysis	Facilitates low-cost, non-invasive diagnosis using smartphone microphones, suitable for large-scale screening and home-based assessment
Physiological time-series data (HR, SpO ₂ , RR, temperature)	Recurrent Neural Networks (RNNs), Long Short-Term Memory (LSTM) models	Early detection of clinical deterioration, chronic disease monitoring, anomaly detection	Supports continuous remote diagnosis by identifying deviations from patient-specific baselines and temporal trends
Multivariate clinical features	Traditional ML models (Random Forest, Support Vector Machine, Logistic Regression)	Risk stratification, disease classification, triage decision support	Provides interpretable diagnostic support, suitable for heterogeneous telemedicine data and resource-constrained deployments
Patient-reported text and clinical narratives	Natural Language Processing (NLP), Transformer-based models	Symptom extraction, automated triage, diagnostic suggestion	Enhance teleconsultations by structuring unstructured patient input and supporting clinician decision-making
Multimodal data (images, vitals, text, demographics)	Multimodal Deep Learning, Ensemble Models	Complex diagnostic reasoning, comorbidity assessment	Improves diagnostic robustness and accuracy by integrating complementary data sources, closely mirroring real-world clinical reasoning

5. MACHINE LEARNING FOR REMOTE PATIENT MANAGEMENT

Remote patient management is an important next step in intelligent telemedicine as it goes beyond the episodic diagnosis approach and moves toward continuous, proactive, and personalised care. Whereas remote diagnosis concerns the determination of disease states at some point in time, remote patient management is about the longitudinal progress of patient health, which includes continuous monitoring, early warning generation, personalised intervention and long-term care optimisation. Machine learning is crucial for enabling these features to function and convert large amounts of diverse and heterogeneous patient data into practical clinical information.

One of the major roles of machine learning for remote patient management is to create early warning models for clinical deterioration prior to acute episodes. ML models can identify subtle patterns and trends before the appearance of symptoms or clinical deterioration by examining time-series collected as part of physiologically relevant information collection processes via IoMT devices. Such models are quite useful in coordinating chronic and several co-morbid patients, since early intervention may avert hospitalisation, reduce health costs, and improve quality of life [5]. Unlike rule-based thresholding systems, ML-based early warning models are patient oriented and generalise to specific patient characteristics at higher sensitivity with respect to risk.

Remote patient management predictive models create patient-specific baselines by modelling historical physiological variables and patterns of behaviour, as well as their contextual information; age, and comorbidity burden, that may or may not be present. Disruptions to such personalised baselines are more clinically relevant, especially among patients with chronic disease. Temporal models like recurrent neural networks and ensemble methodologies analyse longitudinal data to approximate short-term and medium-term risk to provide information from large enough temporal scales that can be deployed, thus can inform the short- and medium-term risk profile to support dynamic prioritisation and escalation on telemedicine platforms. This predictive power allows the clinicians to concentrate on intervention towards high-risk patients, and to avoid being directed at a larger population at risk.

Risk prediction aside, machine learning assists personalised pathways of care, in a recommendation-based model, tailoring the intervention to individual patient profiles and real-time feedback. This combines physiological variables, medication compliance information, lifestyle markers and previous clinical data to prescribe individually tailored interventions such as change treatment regimens (e.g., medication, behavioral nudges, and follow-up regimens) [20]. And this can work well, as patient engagement, adherence and clinical outcomes can be achieved with these factors in an individualised manner with each patient's care plan when personalised for chronic disease control.

It adds a piece of data that is data related to remote patient care which can be further improved through patient engagement metrics which include compliance, adherence and psychosocial wellbeing. Wearable devices evaluate behavioral signals like physical activity, sleep patterns and daily cycles but by analysing it to see how the patients are engaging with the technology, using NLP, it will reveal emotional mood, stress levels and mental health status [6]. Such knowledge has particularly beneficial implications in the treatment of depression, anxiety, and lifestyle-driven diseases, as they are behavior driven and psychologically driven. Machine learning that can deliver behavioural analytics into telemedicine platforms brings a multi-faceted approach to the patient's care, well beyond strict clinical considerations.

In turn, these machine learning-enabled capabilities turn telemedicine from being a reactive, consultation-based service into a continuous and adaptive healthcare model. Machine learning powered remote patient management systems allow longitudinal monitoring and intervene as per current knowledge and allow the delivery of personalised care for sustained health over time with continuous disease management to be achieved. ML-powered remote patient management will thus be vital for enhancing health care systems in this new era driven by value-based and preventive care models, resulting in enhanced patient management and better-managed care systems.

6. CASE STUDIES AND APPLICATIONS

It had been found that intelligent telemedicine systems offer considerable clinical and operational benefits applicable to various areas in healthcare, validating the real-world application of machine learning enabled remote diagnosis and patient management. The experiment demonstrates the feasibility of integrating machine learning models into telemedicine systems. The results represent proof of concept validation rather than final clinical performance.

Tele-dermatology is one of the most well-documented and popular uses of intelligent telemedicine. Based on smartphone image acquisition and integrated with convolutional neural networks, automatic skin lesion evaluation and wound assessment have been provided for online medical imaging of these images as submitted with patients remotely. These systems can also serve as early screening for malignant melanoma and other dermatological diseases, critical for early referral to treatment and prevention, and to minimise in-person consultations with specialists [8]. And in areas where access to dermatologists is limited like those described, tele-dermatology systems have shown great promise at improving access to specialist care and cutting time to diagnosis. ML-based wound monitoring is also consistent with longitudinal tracking of healing process allowing for home-based post-operative and chronic wound treatment.

Intelligent telemedicine is also increasingly becoming a beneficial means of cardiovascular care. Meanwhile, IoMT-based cardiac monitoring systems measure these signals on an ongoing basis, assessing heart rate, heart rhythm, and activity of the heart, amongst other physiological indicators. Machine learning models analyse such streams of data to detect arrhythmia, forecast cardiac exacerbations and to notify clinicians of early clinical decline. Monitoring based on continuous ML for proactive management reduces emergency admissions and supports the outpatient care of chronic heart disease with a more effective outcome. These are great for older patients and people who are the ones at risk and who would require constant supervision but maybe do not have the resources or can't do so.

Management of chronic diseases is the most important application of intelligent telemedicine, in particular diabetes, hypertension, chronic obstructive pulmonary disease (COPD) and asthma. In the tele-management platform glucose results, blood pressure readings, respiration parameters and behaviour data are acquired using IoMT. The longitudinal trajectory is examined by machine learning models, providing personalised patient recommendations and monitoring of adherence, as well as early warning to the patient about follow-up [4], [12]. Studies show that by using ML-assisted tele-management with those results, there were significant reductions in hospital admissions and decrease in morbidity levels as well as the extent of hospitalised patients with higher involvement with lower illness rates and reduced health morbidity [4]. These results are consistent with a broader goal of healthcare, including shifting care from acute hospital contexts to community- and home-based environments.

When integrated into telemedicine platforms, there have also been real benefits for mental health care: machine learning has played a leading role. Speech, voice, and text analytics can also provide automatic assessments of cognitive performance, stress assessment, and mood throughout teleconsultations or asynchronous clinical encounters. Natural language processing models are leveraged in studying patient interactions to understand what types of linguistic data might be associated with depression, anxiety, and other mental health disorders, to underpin scalable screening and digital therapy protocols [6]. Such approaches will be helpful to address both shortages of mental health providers worldwide and the access barriers for disadvantaged patients.

The COVID-19 pandemic is a huge real-world test case for smart telemedicine software. They included high-volume, machine learning-backed triage systems, risk stratification models, and remote monitoring systems to help manage the wide variations in patient numbers while limiting in-person participation. Such systems enabled early detection of high-risk patients, optimised the distribution of health resources, and preserved continuity of care as required to cope with the demand of patients at the time. Deployments during the pandemic era have reinforced the need for scalable, ML-enabled telemedicine infrastructures in terms of resilience of healthcare systems.

Overall, these cases reflect that intelligent telemedicine systems are not only conceptual, they are also practical and medically relevant tools who already started disrupting the way in which healthcare is delivered. In several areas, machine learning-based telemedicine platforms have proven to enhance access, diagnosis and treatment, as well as providing a springboard for future sustainable patient-centred care models.

7. MACHINE LEARNING WORKFLOW AND RESULTS

To empirically evaluate, a proof-of-concept workflow was established demonstrating a practical implementation of machine learning in smart telemedicine systems using an IoMT-like patient data for short-term prediction of patient decline. This experimental goal was not to find algorithmic-level optimisation on its own, but to demonstrate that a machine learning pipeline based in telemedicine architecture can aid early warning, prioritisation, and proactive patient management.

There are several interdependent phases in this workflow (data pre-processing, feature development, model choice and training, performance testing and clinical inference). These stages are part of the generic end-to-end machine learning lifecycle which a healthcare machine will encounter since predictive accuracy must be addressed in addition to interpretability, robustness, and clinical acceptability. This method workflow, illustrated in Figure 2, is a basic framework for the methodological discussion in this section.




Figure 2. Machine Learning Workflow for Remote Patient Risk Prediction in Telemedicine

In this study, we implemented synthetic training of data sets with IoMT telemedicine from similar physiological, behavioral and demographic characteristics. These encompassed heart rate, oxygen saturation, respiratory rate, body temperature, systolic blood pressure, physical activity levels, age and comorbidity count. These variables were selected because their prevalence is common in remote monitoring contexts and it has now been recognised that their clinical deterioration risk is well established. Following usual preprocessing steps (including filling in missing data, numerical feature normalisation, and feature distribution preprocessing) prior to training, we focused on maintaining the general distributions of various features of simulated patients.

To ensure reproducibility, the experimental protocol is reported as follows. (i) Synthetic data-generation method: each simulated patient record was generated programmatically. Age was sampled uniformly between 18 and 90 years, and comorbidity count was drawn from a Poisson distribution whose mean increased with age ($0.4 + 0.035 \times [\text{age} - 18]$, capped at 8). A latent physiological-severity variable, which increased with age and comorbidity burden, was then used to generate correlated values for heart rate, SpO₂, respiratory rate, body temperature and systolic blood pressure (truncated normal distributions within physiologically plausible limits) and for daily step count (log-normal, decreasing with severity). Each sensor-derived value had a 5% probability of being set to missing completely at random to mimic intermittent wearable-device data, and no real patient records were used at any stage. (ii) Sample size: the dataset comprised 2,000 simulated patients, one record per patient. (iii) Class distribution: 542 patients (27.1%) were labelled high risk and 1,458 (72.9%) low/normal risk. (iv) Label generation: each patient received an early-warning score that combined NEWS2-style points for respiratory rate, SpO₂, systolic blood pressure, heart rate and body temperature with additional points for low daily activity (fewer than 2,000 steps: 3; 2,000–3,999: 2; 4,000–5,999: 1), age of 65 years or above (1) and three or more comorbidities (1). Patients scoring 4 or above were labelled high risk, and 5% of labels were then randomly flipped to emulate clinical uncertainty. Labels were derived from the complete values before missingness was introduced. (v) Software and random seed: data generation and modelling were performed in Python 3.13 using NumPy 2.5, pandas 3.0 and scikit-learn 1.9. A fixed random seed of 42 was used

for data generation, the train/test split and the random forest classifier (200 trees, with the remaining hyperparameters at library defaults). (vi) Train/test procedure: the dataset was divided into a stratified 70% training set ($n = 1,400$) and a 30% held-out test set ($n = 600$). Median imputation and standardisation were fitted on the training set only and then applied to the test set, and all metrics in Table 2 were computed once on the held-out test set.

A random forest classifier was implemented as the predictive model which is considered a good fit for heterogeneous clinical data and can capture non-linearity with little parameter update. The random forest models are interpretable based on estimating feature importance meaning that the feature importance is critical in clinical decision support as transparency and trust are important components of decision support. More advanced deep learning-based models might also obtain marginal performance improvements; however the proposed approach seems most practical when it comes to balancing the parameters of performance, interpretability and deployment in telemedicine systems.

The model's generalisation performance was measured with a held-out test set. The dataset was split up between a 70% training and 30% test set. The accuracy of the classification is 89.3%, with a high degree of agreement between predicted and true risk categories. Lastly, the receiver operating characteristic area under the curve (ROC-AUC) for the model was 0.911, indicating that the model demonstrated an excellent discrimination between low-risk and high-risk patients. These results also suggest that the model could also be able to prioritise patients that may require even more closely supervised or clinically tailored treatments. These are imperative in a remote patient management setting.

Feature importance added to the overall performance measures and clinical drivers of model prediction. Physical activity level was the single most important predictor based on number of steps taken, followed by oxygen saturation, respiratory rate, systolic blood pressure, heart rate, age, body temperature and comorbidity burden. This is consistent with clinical use of deceleration of mobility which results in reduced oxygen saturation before acute illness, especially in elderly or chronic disease patients. The model-dependent feature value of importance is aligned with clinical intuition validation, and it justifies the approach, making it a highly interpretable algorithm.

The model's accuracy, recall, F1-score, confusion matrix value was summarised in Table 2 and further addressed in this section to reinforce quantitative analysis of the predictive model.

Table 2. Performance Metrics for Remote Patient Risk Prediction Model

Metric	Value	Interpretation in Telemedicine Context
Accuracy	0.893	Indicates strong overall correctness in classifying low-risk and high-risk patients
Precision (Low / Normal Risk)	0.898	High reliability in identifying patients who are truly low risk
Recall (Low / Normal Risk)	0.963	Effectively captures the majority of low-risk patients without unnecessary escalation
Precision (High Risk)	0.878	High confidence that patients flagged as high risk genuinely require attention
Recall (High Risk)	0.706	Demonstrates effective detection of high-risk patients, with emphasis on minimising false negatives
F1-Score (High Risk)	0.782	Balanced performance between precision and recall for clinically critical high-risk cases
ROC-AUC	0.911	Excellent discrimination capability between low-risk and high-risk patient groups

In a telemedicine context, the findings provide evidence that machine learning models can be integrated into clinician dashboards to derive actionable risk scores and alerts. Rather than supplanting clinical judgement, such models provide decision-support resources that help clinicians concentrate attention, allocate resources on the clinical agenda, and intervene early in the patient's care. Our results also highlight interpretability and clinically relevant feature selection as key features for promoting trust and for the deployment of AI-driven telemedicine systems.

Collectively, the presented proof-of-concept implementation demonstrates that machine learning–based early warning systems can be successfully incorporated into intelligent telemedicine platforms. While the synthetic nature of the data displayed is a limitation, the workflow process and the outcomes provide potential proof-of-concept tests for incorporation into real IoMT data when validated, regulated and controlled ethically.

8. DISCUSSION

The findings of this research demonstrate that intelligent telemedicine systems present exciting clinical applications, although transitioning from proof-of-concept to clinical implementation presents significant technical, ethical and regulatory hurdles. The synthetic data used in the current study, simulating realistic IoMT conditions, is considered the main limitation. The application of these technologies in simulating real clinical environments allows controlled experimentation and methodological modeling but is not enough to mitigate the noise, heterogeneity, and multifaceted interactions of the real clinical setting. The dataset was designed to simulate the typical settings of remotely monitored IoMT, which involves real-time monitoring of patient physiological signs with wearable devices. These variables are derived from clinically meaningful indicators commonly used in telemedicine scenarios (e.g. vital signs and behavioral activity indicators). By doing so, synthetic datasets allowed for controlled experiments while bypassing the privacy and regulatory issues involved in managing genuine patient data. However, this paper now states that future validation using real-world datasets is needed to indicate generalisability of said model. As a result, performance metrics reported here must be considered as indicative of system performance rather than as definite evidence of real-world utility. Given the above, future research must give priority to validation with real-world data sets, long-term and prospective clinical studies bridging the theory and reality in practice.

Reliability and robustness are the most common technical considerations in relation to such systems. As these telemedicine platforms rely on consumer-grade IoMT devices and wearable sensors in healthcare settings, they are generally unreliable in terms of precision, calibration and longevity. Patient behaviors (e.g., infrequent device usage; incorrect placement of sensors, etc.) and other environmental variables (lighting, background sound) weaken the performance of inputs utilised to infer machine learning. This can lead to data sets that are noisy or missing, potentially harming the quality of models and hence their robustness and in turn leading to high false alarms or errors in clinical settings in this domain. It remains an open question, connecting data integrity issues to issues here, to what technical solutions for safety and fidelity to automated clinical decision support safety can be possible.

And ethical aspects are often as ingrained, as embedded as the technical ones: algorithmic bias and the data privacy issues. The non-representative models can differ and/or make unfair predictions for some segments of the population (e.g., the elderly population or racial-ethnic minority groups) and are even more harmful to health inequalities occurring in the health care market. In an integrated telemedicine setting with widespread telemedicine provider deployment, individual sample bias may result in differential diagnosis (or risk ranking) based on human characteristics. Moreover, because the data collection is very dispersed and related to the telemedicine sector, cyber threats are also aggravated, as IoMT devices, home networks and clouds are at risk of data misuse or unauthorised access [12]. Strong encryption techniques, secure authentication, and security over a specified schedule and duration of surveillance to ensure patient confidence and privacy in sensitive health data are key to ensuring patient trust and privacy in sensitive patient information.

Data interpretation of machine learning models can also greatly contribute to clinical confidence of clinicians and regulatory approval process. On the one hand, deep learning models have good potential to perform in the prediction task domain, but they are black boxes and must be applicable on high-impact diagnostics or triage tasks including the rationale for the work. Such AI approaches must be explainable to ensure transparency and to enable clinicians to interpret and thus validate the model outputs. And the argument for transparency is entangled in other thorny regulatory/legal issues around how those same data are governed in that system, ranging from who is responsible for such AI-driven decision making. Systems serve thousands of jurisdictions, so catering to them in various legislations and figuring out what accountability a system has for the work of clinicians, organisations, and creators is continuous work in progress. Making informed consent even more difficult is the issue that patients are not supposed to sense how their data is being used to train or otherwise use such models. Therefore, transparency must be ensured if patient autonomy is to be honored.

Further development of intelligent telemedicine is likely to be driven by advancements that can potentially overcome these limitations soon through much-improved personalisation and autonomy. Digital twin technology also presents an attractive opportunity for personalised care by simulating disease evolution and treatment response in the context of scenario-based decision-making in complex chronic care. At the same time federated learning may be a relevant advancement concerning privacy and data governance. With federated learning, the platform can better capture and integrate diverse human populations. This can be done by bypassing the necessity to centralise raw patient data and enable models to learn by doing it together across a range of distributed data sources under very strict privacy standards.

Explainable artificial intelligence will remain critical to the adoption and acceptance of future AI models, and must be explained not only as technically sound, but clinically important. Collectively, thanks to our interpretability gains, emotion-aware and affect-sensitive AI agents represent a new frontier. By examining speech patterns, facial expressions and behavioral indicators, as well as psychological states, such systems could gain insight into mental health that could assist mental health assessment and form the therapeutic relationship using a more empathetic digital framework. It is possible to embed such capabilities as multimodal learning architectures that leverage physiological responses, genomic data, and social determinants of health to enhance diagnostic accuracy and robustness when cases are multifaceted and/or comorbid.

For the deployment within this environment, the infrastructure required to support edge intelligence and autonomous IoMT ecosystems will be essential to achieving scalable, low-latency deployments. This means that edge-based machine learning can achieve near-to-location near real-time data generation instead of dependency on continuous network connectivity through the cloud that promotes resilience in bandwidth-capped environments. These become significantly harder to enable than just optimising for technology, in essence driving a legislative change towards adaptive, learning-based systems. Moving forward, continuous model updating, cross-border data flows and cross-border challenges associated with continuous model updating, longitudinal data flows and continuous learning-based system vetting will also play a major role in governance. Thus, close collaboration of regulators, clinicians, and technologists which will be critical will ensure that intelligent telemedicine technology comes to act as an anticipatory, continuous and personalised service, in which the individual will be personalised and continuously improving his or her health outcomes, without violating trust or equity thresholds.

9. CONCLUSION

Intelligent telemedicine systems are transitioning healthcare fields from primitive communication and data-based systems toward composite ones. These combine the strengths of machine learning, Internet of Medical Things (IoMT) and cloud-edge computing into a powerful form of diagnostics. These systems are thus leading the way right up to proactive diagnoses, continuous monitoring, personalised treatments and population health management. This transition can be seen as a response to a variety of major global problems such as an ageing population, chronic diseases, a shortage of staff and soaring living costs. We illustrate the application of machine learning in clinical decision-making through the integration of medical imaging, the interpretation of physiological signals, natural language processing, and multimodal information integration. A case study of a predictive workflow demonstrates the advantage of interpretable models, which align best with clinical knowledge and play a well-suited role in decision support. But to do so in practice, you also must properly consider data quality, bias, transparency, security, regulation and ethics. Trust, accountability, equity and patient autonomy in the context, especially in the age of algorithmic supremacy, loom large. Emerging directions such as digital twins, federated learning, explainable AI, emotion-aware interfaces and autonomous IoMT systems are not just an extension of this line of thinking, but they are all subject to collaborative arrangements between clinicians, engineers, data scientists, policymakers and ethicists. Hence, intelligent telemedicine can be crucial to encourage preventive and patient-oriented value-based care for improved treatment, creating opportunities and helping underpin sustainable global health systems change.

ACKNOWLEDGEMENT

The authors would like to thank the anonymous reviewers for the suggestions to improve the paper.

FUNDING STATEMENT

This research received no funding.

AUTHOR CONTRIBUTIONS

Oras Baker: Conceptualisation, Data Curation, Methodology, Writing – Original Draft Preparation;
Kasthuri Subaramaniam: Project Administration, Supervision, Methodology, Writing – Review & Editing;
Asiah Lokman: Methodology, Validation, Writing – Review & Editing;

CONFLICT OF INTERESTS

No conflict of interests were disclosed.

ETHICS STATEMENTS

This research did not require Institutional Review Board (IRB) approval because it used only a fully synthetic, computer-generated dataset; no real patient data, human participants or identifying personal information were involved.

DATA AVAILABILITY

The synthetic dataset and the code used to generate it are available from the corresponding author on request.

REFERENCES

- [1] L. C. Schünke, B. Mello, C. A. da Costa, R. S. Antunes, S. J. Rigo, G. de O. Ramos, R. da R. Righi, J. N. Scherer, and B. Donida, “A rapid review of machine learning approaches for telemedicine in the scope of COVID-19,” *Artif. Intell. Med.*, vol. 129, p. 102312, 2022, doi: 10.1016/j.artmed.2022.102312.
- [2] N. M. Sarkar, N. R. Dey, and N. M. T. Mia, “Artificial intelligence in telemedicine and remote patient monitoring: Enhancing virtual healthcare through AI-driven diagnostic and predictive technologies,” *Int. J. Sci. Res. Arch.*, vol. 15, no. 2, pp. 1046–1055, 2025, doi: 10.30574/ijrsra.2025.15.2.1402.
- [3] M. Rossi and S. Rehman, “Integrating artificial intelligence into telemedicine: Evidence, challenges, and future directions,” *Cureus*, vol. 17, no. 8, 2025, doi: 10.7759/cureus.90829.
- [4] U. Chaturvedi, S. B. Chauhan, and I. Singh, “The impact of artificial intelligence on remote healthcare: Enhancing patient engagement, connectivity, and overcoming challenges,” *Intelligent Pharmacy*, vol. 3, no. 5, pp. 323–329, 2025, doi: 10.1016/j.ipha.2024.12.003.
- [5] S. Khadse, P. Verma, and V. Lande, “Artificial intelligence and machine learning in telemedicine: Transforming remote healthcare,” in *Proc. Int. Conf. Mach. Learn. Auton. Syst. (ICMLAS)*, 2025, pp. 508–514, doi: 10.1109/ICMLAS64557.2025.10968984.
- [6] P. Sharma, “Smart healthcare: The role of AI, robotics, and NLP in advancing telemedicine and remote patient monitoring,” *BMC Artif. Intell.*, vol. 1, no. 1, p. 14, 2025, doi: 10.1186/s44398-025-00015-4.

- [7] O. Baker, Z. Ziran, M. Mecella, K. Subaramaniam, and S. Palaniappan, "Predictive modeling for pandemic forecasting: A COVID-19 study in New Zealand and partner countries," *Int. J. Environ. Res. Public Health*, vol. 22, no. 4, p. 562, 2025, doi: 10.3390/ijerph22040562.
- [8] J. G. Fernandes, "Artificial intelligence in telemedicine," in *Artificial Intelligence in Medicine*, Cham, Switzerland: Springer, 2022, pp. 1219–1227, doi: 10.1007/978-3-030-64573-1_93.
- [9] O. Baker, Z. Ziran, M. Mecella, and K. Subaramaniam, "AI-driven melanoma detection in New Zealand: A ResNet50-based approach," *Inform. Med. Unlocked*, vol. 58, p. 101697, 2025, doi: 10.1016/j.imu.2025.101697.
- [10] S. Palaniappan, R. Logeswaran, K. Subaramaniam, O. Baker, and B. N. Dung, "Training the brain: A machine learning approach to predicting wellbeing through intentional thought pattern modification," *J. Inform. Web Eng.*, vol. 4, no. 3, pp. 64–89, Oct. 2025, doi: 10.33093/jiwe.2025.4.3.4.
- [11] O. Baker, K. Subaramaniam, A. S. B. Shibghatullah, Z. A. Shaffiei, and A. S. S. S. Amir Hamzah, "A collaborative framework for disease prediction using machine learning," in *Proc. IEEE Int. Conf. Artif. Intell. Eng. Technol. (IICAET)*, 2025, pp. 650–654, doi: 10.1109/IICAET67254.2025.11265309.
- [12] V. K. Damera, R. Cheripelli, N. Putta, G. Sirisha, and D. Kalavala, "Enhancing remote patient monitoring with AI-driven IoMT and cloud computing technologies," *Sci. Rep.*, vol. 15, no. 1, p. 24088, 2025, doi: 10.1038/s41598-025-09727-z.
- [13] G. Sannino, A. Celesti, and I. De Falco, "Special Issue: 'Intelligent Systems for Clinical Care and Remote Patient Monitoring'," *Sensors*, vol. 23, no. 18, p. 7993, 2023, doi: 10.3390/s23187993.
- [14] K. Perez, D. Wisniewski, A. Ari, K. Lee, C. Lieneck, and Z. Ramamonjiarivelo, "Investigation into application of AI and telemedicine in rural communities: A systematic literature review," *Healthcare*, vol. 13, no. 3, p. 324, 2025, doi: 10.3390/healthcare13030324.
- [15] S. Y. Kadum, O. H. Salman, Z. K. Taha, A. B. Said, M. A. M. Ali, Q. S. Qassim, M. I. Aal-Nouman, D. Y. Mohammed, B. M. Al Baker, and Z. A. Abdalkareem, "Machine learning-based telemedicine framework to prioritize remote patients with multi-chronic diseases for emergency healthcare services," *Netw. Model. Anal. Health Inform. Bioinform.*, vol. 12, no. 1, p. 11, 2023, doi: 10.1007/s13721-022-00407-w.
- [16] H. Faris, M. Habib, M. Faris, H. Elayan, and A. Alomari, "An intelligent multimodal medical diagnosis system based on patients' medical questions and structured symptoms for telemedicine," *Inform. Med. Unlocked*, vol. 23, p. 100513, 2021, doi: 10.1016/j.imu.2021.100513.
- [17] M. Awais, S. S. Fatima, and J. Iqbal, "Review on secure and efficient IoT-based healthcare system with the integration of machine learning and firewalls," *J. Inform. Web Eng.*, vol. 4, no. 3, pp. 140–152, Oct. 2025, doi: 10.33093/jiwe.2025.4.3.8.
- [18] Palaniappan, S., Logeswaran, R., Subaramaniam, K., Baker, O., & Dung, B. N. (2026). Synthetic Data Generation for Healthcare Machine Learning: A Case Study in Vital Signs and Diagnostic Predictions. *Journal of Informatics and Web Engineering*, 5(2), 1–33. DOI: 10.33093/jiwe.2026.5.2.1.
- [19] J. Wolber, A. Schuppert, M. Mücke, et al., "Predicting disease outcomes from remote monitoring using machine learning: A systematic review," *BMC Medical Informatics and Decision Making*, vol. 26, art. 145, 2026. doi: 10.1186/s12911-026-03495-0.
- [20] M. Tsirintani, P. Lialiou, and P. Gallos, "The Impact of Telemedicine and Artificial Intelligence on Healthcare Quality," *Studies in Health Technology and Informatics*, vol. 338, pp. 678–682, 2026. doi: 10.3233/SHTI260931

BIOGRAPHIES OF AUTHORS

	Oras Baker is an Associate Professor and Head of Masters in Cyber Security and Cyber Security Management at University of Ravensbourne London, UK. With 25 years of distinguished experience spanning academia, research, and industry, he specialises in Artificial Intelligence, Software Engineering, Cyber Security, Data Mining, and Machine Learning. He may be contacted at o.alhassani@rave.ac.uk.
	Kasthuri Subaramaniam is a Senior Lecturer at the Department of Decision Science, Faculty of Business and Economics, Universiti Malaya. Her research interests include human-computer interaction, human personality types, augmented reality, artificial intelligence and cybersecurity. She actively serves as a reviewer for refereed journals. She may be contacted at s_kasthuri@um.edu.my.
	Asiah Lokman is an Associate Professor at Malaysia University of Science and Technology. Her expertise spans in Information Technology, IoT, AI, Blockchain, and Telecommunications. She has over 10 years of experience in higher education and has published research articles in reputable journals and conferences. She may be contacted at asiah@must.edu.my.